

Ashmore

Porcelain wood effect - decorative parquet format

Ashmore interprets traditional parquet in a light oak-toned porcelain tile. Layered timber graphics within the square format create the character of an intricate panelled floor while retaining the durability and straightforward maintenance of porcelain.



COLOURS



Drift

Light oak

AVAILABLE FORMAT

600 x 600 mm

8.8 mm porcelain, Matt, non-rectified and R9.

Application: Interior floors and walls. For wet or slip-sensitive areas, please contact Appleton Brooks for advice.

Ashmore

Product-specific technical specification

SPECIFICATION TABLE

Size	Finish	Thickness	Colour availability	Rectified	R Classification DIN 51130	V-Shade
600 x 600 mm	Matt	8.8 mm	Drift	No	R9	V4

R9 is the published shod-ramp classification for the promoted Ashmore product. The promoted product is classified V4 for shade variation. No British Pendulum Test value or barefoot classification is published, and none is inferred.

SPECIFICATION NOTES

- Ashmore Drift is a single-format 600 x 600 mm porcelain tile with an 8.8 mm Matt surface.
- The promoted product is non-rectified and classified R9 / V4.
- This datasheet covers the currently promoted Appleton Brooks Ashmore product only.
- For advice on selecting the most appropriate product for your project, please contact Appleton Brooks.

ENVIRONMENTAL CREDENTIALS

Environmental Product Declaration

Verified EPD

Global Environmental Product Declaration coverage is held for the production source.

Environmental management

ISO 14001

Production operates within a certified environmental management system.

Energy management

ISO 50001

Certified energy-management systems support monitoring and reduction of energy use.

Supporting documentation is available on request where appropriate.