Avenor

Limestone-effect porcelain - softened mineral character

Avenor draws on the quiet character of limestone, with finely dispersed grain and gentle shifts in tone. Dove, Rye, Putty and Quarry form a restrained mineral palette that sits naturally alongside timber, plaster and stone. Three rectified Matt formats offer a composed surface for contemporary interiors.



COLOURS

Dove
Pale ivory

Rye
Warm beige

Putty
Soft greige

Quarry
Cool grey

AVAILABLE FORMATS

300 × 600mm / 600 × 600mm / 600 × 1200mm

Matt only · 8mm thick · Rectified · All four colours

Application: Internal floor and wall tiling; verify suitability for project conditions.

Avenor

Matt porcelain - technical specification

FLOOR AND WALL TILE SPECIFICATION

Size	Finish	Thickness	Colour availability	Rectified	PTV BS EN 16165 Annex C	R classification DIN EN 16165 Annex B	Barefoot DIN EN 16165 Annex A
300 × 600mm	Matt	8mm	All four colours	Yes	≥36 Dry ≥36 Wet	R10	A+B
600 × 600mm	Matt	8mm	All four colours	Yes	≥36 Dry ≥36 Wet	R10	A+B
600 × 1200mm	Matt	8mm	All four colours	Yes	≥36 Dry ≥36 Wet	R10	A+B

The pendulum test (BS EN 16165 Annex C), shod-ramp test (DIN EN 16165 Annex B) and barefoot test (DIN EN 16165 Annex A) are independent assessments and must not be treated as interchangeable.

SPECIFICATION NOTES

- The results shown apply to the Matt surface and the three formats promoted by Appleton Brooks.
- For advice on selecting the most appropriate finish for your project, please contact Appleton Brooks.
- V3 denotes moderate tonal variation; review representative samples before final specification.