APPLETON BROOKS

TECHNICAL DATASHEET

Calder

Rectified porcelain - softly mottled mineral character

Calder explores the softly mottled character of mineral surfaces through four quiet, versatile tones. Its subtle tonal movement creates a considered backdrop for contemporary residential and project-led interiors, sitting naturally alongside timber, plaster and contrasting materials.



COLOURS

Pumice
Pale ivory

Oatfield
Warm beige

Silt
Balanced greige

Graphite
Cool grey

AVAILABLE FORMATS

300 × 600mm / 600 × 600mm / 600 × 1200mm

All four colours are promoted in the Matt finish only.

Application: Internal and external walls and floors; project suitability to be assessed against installation conditions.

Calder

Matt finish technical specification

SPECIFICATION TABLE

Size	Finish	Colour availability	Rectified	PTV BS EN 16165 Annex C	R Class EN 16165 Annex B	Barefoot EN 16165 Annex A
300 × 600mm	Matt	All four colours	Yes	≥36 dry & wet	R10	A+B
600 × 600mm	Matt	All four colours	Yes	≥36 dry & wet	R10	A+B
600 × 1200mm	Matt	All four colours	Yes	≥36 dry & wet	R10	A+B

PTV, R and barefoot classifications are independent test results. Values refer to the Matt finish only; see source manufacturer test schedule (2025).

SPECIFICATION NOTES

- Matt finish is promoted across all four colours and three sizes; specialist finishes are excluded from this datasheet.
- For advice on selecting the most appropriate finish for your project, please contact Appleton Brooks.
- Check the intended use, site conditions and installation method with the project designer.