APPLETON BROOKS

TECHNICAL DATASHEET

Marlowe

Porcelain stone effect - layered mineral tones

Marlowe brings quiet mineral character to six porcelain shades. Matt formats suit floors and walls, with selected Grip, 20mm Textured, slab and sculpted Carved options.



COLOURS

Umber
Warm greige

Sandbank
Warm sand

Albedo
Pale ivory

Alloy
Soft mineral grey

Serein
Cool grey

Cinder
Deep charcoal

AVAILABLE FORMATS

300 x 600mm / 600 x 600mm / 600 x 1200mm / 1200 x 1200mm

Application: Floors and walls by finish; Carved is for walls only.

Marlowe

Format- and finish-specific technical specification

FLOOR TILE SPECIFICATION

Size	Finish	Thickness	Colour availability	Rectified	PTV BS EN 16165 C	R rating DIN EN 16165 B	Barefoot DIN EN 16165 A
300 x 600mm	Matt	8.5mm	All six colours	Yes	≥36 Dry / Wet	R10	A+B
600 x 600mm	Matt	8.5mm	All six colours	Yes	≥36 Dry / Wet	R10	A+B
600 x 1200mm	Matt	8.5mm	All six colours	Yes	≥36 Dry / Wet	R10	A+B
1200 x 1200mm	Matt	9mm	All six colours	Yes	≥36 Dry / Wet	R10	A+B
1200 x 2780mm	Matt slab	6mm	Sandbank, Albedo, Alloy, Serein	Yes	—	R9	—
600 x 1200mm	Grip	8.5mm	Sandbank, Albedo, Alloy, Serein	Yes	≥36 Dry / Wet	R11	A+B+C
600 x 1200mm	20mm Textured	20mm	Sandbank, Albedo, Alloy, Serein	Yes	≥36 Dry / Wet	R11	A+B+C
600 x 600mm	20mm Textured	20mm	Sandbank, Albedo, Serein	Yes	≥36 Dry / Wet	R11	A+B+C

PTV, R classification and barefoot are separate tests. Standards: BS EN 16165 Annex C; DIN EN 16165 Annex B and Annex A respectively.

CARVED - WALL TILE ONLY

Size	Finish	Thickness	Colour availability	Rectified
600 x 1200mm	Carved (3D Matt)	8.5mm	Sandbank, Albedo, Alloy, Serein	Yes

SPECIFICATION NOTES

- Slip ratings vary by finish. A dash indicates a value not published for the 1200 x 2780mm slab; Carved is for wall use only.
- For advice on selecting the most appropriate finish for your project, please contact Appleton Brooks.