

Twine

Porcelain wood effect - rectified plank collection

Twine brings the warmth and grain variation of timber into a durable porcelain surface. The collection is offered in two natural wood tones and two rectified plank formats, creating a calm, continuous finish for interiors where the appearance of wood is required with the practicality of porcelain.




COLOURS



Pecan

Light oak



Bark

Warm brown

AVAILABLE FORMAT

100 x 600 mm / 200 x 1200 mm

Both promoted formats are 9.5 mm, Matt, Rectified and R10.

Application: Interior floors and walls. Contact Appleton Brooks where slip-sensitive or external use is being considered.

Twine

Format-specific technical specification

SPECIFICATION TABLE

Size	Finish	Thickness	Colour availability	Rectified	R Classification DIN 51130
100 x 600 mm	Matt	9.5 mm	Pecan / Bark	Yes	R10
200 x 1200 mm	Matt	9.5 mm	Pecan / Bark	Yes	R10

R10 to DIN 51130 is published for the promoted Twine formats. No PTV or barefoot value is published and none is inferred.

SPECIFICATION NOTES

- Both promoted formats are 9.5 mm, Matt, Rectified and R10.
- R10 is the published DIN 51130 classification and should not be treated as equivalent to a PTV value.
- This datasheet covers the currently promoted Appleton Brooks Twine formats only.
- For advice on selecting the most appropriate Twine product for your project, please contact Appleton Brooks.

ENVIRONMENTAL CREDENTIALS

Environmental Product Declaration

Verified EPD

Environmental Product Declaration reporting is stated as compliant with ISO 14025 and EN 15804.

Carbon footprint

ISO 14067

Product carbon-footprint reporting is stated as compliant with ISO 14067.

Supporting documentation is available on request where appropriate.